

ZOOMLION

SCISSOR LIFTS

Li-ion SERIES

Comply with ANSI Standard

HIGHLIGHTS

Cutting-Edge Driving System with Lithium Power

- ▶ 5-year warranty for Li-ion battery
- ▶ Maintenance-free and durable Li-ion battery with triple longer lifetime than traditional
- ▶ Quick-charge technology save time
- ▶ Preheating function built in for cold weather regions
- ▶ Smart Battery Management System (BMS) guarantees safety power.

FEATURES

Standard Features

BMS(Battery Management System)	On-board diagnostic
Proportional controls	Over tilt protective system
All motion alarm	Active pothole protection system
Fold-down handrails	Drivable at full height
Flashing amber beacon	Hour meter
Self-closing entry gate	Extension deck (unidirectional)
Autobrake system	Charging protection system
Emergency descent system	Scissor maintenance prop
Emergency stop button	Forklift pockets

Accessories & Options

- ▶ Platform work lights
- ▶ Load sensing system
- ▶ AC power to platform
- ▶ Airline to platform
- ▶ Horn

NASH

PLANT GROUP

Sales & Hire

1 3 0 0 6 2 7 4 7 4



ACCESS WITH ZOOMLION GREEN

Hotline: +86 400-800-0157
E-mail: awm@zoomlion.com

Add: ZOOMLION Wangcheng Industrial Park, Tengfei Road 997, Changsha, Hunan, China.
Learn more at <http://en.zoomlion.com/>

MAIN SPECS OF SCISSOR LIFTS

DC-Li

Comply with ANSI Standard

Model	ZS0607DC-Li		ZS0608DC-Li		ZS0808DC-Li		ZS1012DC-Li		ZS1212DC-Li		ZS1414DC-Li	
	Imperial	Metric	Imperial	Metric	Imperial	Metric	Imperial	Metric	Imperial	Metric	Imperial	Metric
Size												
Work Height	25ft 7in	7.8m	26ft 3in	8.00m	32ft 10in	10.00m	38ft 9in	11.80m	45ft 3in	13.80m	51ft 6in	15.7m
A-Platform Height-Elevated	19ft	5.8m	19ft 8in	6.00m	26ft 3in	8.00m	32ft 2in	9.80m	38ft 9in	11.80m	44ft 11in	13.7m
B-Platform Height-Stowed	3ft 5in	1.05m	3ft 6in	1.07m	3ft 11in	1.20m	4ft 4in	1.33m	4ft 10in	1.46m	5ft	1.53m
C-Platform Length	5ft 5in	1.65m	7ft 7in	2.30m	7ft 7in	2.30m	7ft 7in	2.30m	7ft 7in	2.30m	8ft 9in	2.67m
D-Platform Width	2ft 5in	0.74m	2ft 8in	0.81m	2ft 8in	0.81m	3ft 8in	1.12m	3ft 8in	1.12m	3ft 8in	1.12m
Platform Extension	3ft	0.91m	3ft	0.91m	3ft	0.91m	3ft	0.91m	3ft	0.91m	3ft	0.9m
E-Overall Height (Rails Up)	7ft 3in	2.20m	7ft 4in	2.22m	7ft 9in	2.35m	8ft 1in	2.46m	8ft 6in	2.59m	8ft 8in	2.65m
Overall Height (Rails Down)	5ft 10in	1.79m	5ft 8in	1.72m	6ft 1in	1.85m	6ft 4in	1.92m	6ft 9in	2.05m	6ft 11in	2.1m
F-Overall Length	6ft 1in	1.85m	8ft 2in	2.49m	8ft 2in	2.49m	8ft 2in	2.49m	8ft 2in	2.49m	9ft 5in	2.87m
G-Overall Width	2ft 6in	0.76m	2ft 8in	0.81m	2ft 8in	0.81m	3ft 9in	1.15m	3ft 9in	1.15m	4ft 7in	1.4m
H Wheelbase	4ft 6in	1.37m	6ft 1in	1.85m	6ft 1in	1.85m	6ft 1in	1.85m	6ft 1in	1.85m	7ft 3in	2.22m
I-Ground Clearance (Stowed)	2.4in	0.06m	4.5in	0.11m	4.5in	0.11m	4.5in	0.11m	4.5in	0.11m	4.5in	0.11m
J-Ground Clearance (Raised)	0.65in	0.016m	0.75in	0.02m	0.75in	0.02m	0.75in	0.02m	0.75in	0.02m	0.75in	0.02m
Performance												
Platform Capacity	510lb	230kg	840lb	380kg	510lb	230kg	770lb	350kg	770lb	350kg	570lb	260kg
Capacity on Deck Extension	250lb	113kg	250lb	113kg	250lb	113kg	250lb	113kg	250lb	113kg	250lb	113kg
Max. Number of Workers	2		2		2		2		3		2	
Drive Speed (Stowed)	2.5mph	4km/h	2.5mph	4km/h	2.5mph	4km/h	2.5mph	4km/h	2.5mph	4km/h	2.5mph	4km/h
Drive Speed (Raised)	0.5mph	0.8km/h	0.5mph	0.8km/h	0.5mph	0.8km/h	0.5mph	0.8km/h	0.5mph	0.8km/h	0.5mph	0.8km/h
Turning Radius (Inside)	4in	0.1m	4in	0.1m	4in	0.1m	4in	0.1m	4in	0.1m	4in	0.1m
Turning Radius (Outside)	5ft 3in	1.6m	6ft 11in	2.1m	6ft 11in	2.1m	7ft 3in	2.2m	7ft 3in	2.2m	8ft 6in	2.6m
Drive Motor	24V/2x0.65KW		24V/2x0.75KW		24V/2x0.75KW		24V/2x0.75KW		24V/2x0.75KW		24V/2x0.75KW	
Up/Down Time	20s/24s		28s/35s		31s/40s		60s/35s		62s/42s		88/60s	
Gradeability	25%(14°)		30%(17°)		25%(14°)		25%(14°)		25%(14°)		25%	
Max. Working Slope (Lateral/Vertical)	1.5°/3°		1.5°/3°		1.5°/3°		1.5°/3°		1.5°/3°		1.5°/3°	
Control	Proportional Control		Proportional Control		Proportional Control		Proportional Control		Proportional Control		Proportional Control	
Drive	Front Wheels		Front Wheels		Front Wheels		Front Wheels		Front Wheels		Front Wheels	
Brake	Front Wheels		Front Wheels		Front Wheels		Front Wheels		Front Wheels		Front Wheels	
Tire	Ø13in x4in	Ø323mm x100mm	Ø15in x5in	Ø381mm x127mm	Ø15in x5in	Ø381mm x127mm	Ø15in x5in	Ø381mm x127mm	Ø15in x5in	Ø381mm x127mm	Ø15in x5in	Ø381mm x127mm
Power												
Battery	140Ah Li-ion		180Ah Li-ion		180Ah Li-ion		200Ah Li-ion		200Ah Li-ion		250Ah Li-ion	
Charger	24V/30A		24V/30A		24V/30A		24V/30A		24V/30A		24V/30A	
Charger (Option)			24V/60A		24V/60A		24V/60A		24V/60A		24V/60A	
Weight												
Gross	3210lb	1455kg	4280lb	1940kg	4610lb	2090kg	6460lb	2930kg	7075lb	3210kg	7870lb	3570kg

