

ZOOMLION TELESCOPIC BOOM LIFTS

Comply with CE/ANSI/GB Standard

FEATURES

Standard Features

- Horn
- All motion alarm
- Proportional control
- Self-closing entry gate
- Flashing amber beacon
- GPS positioning and tracking system
- Remote monitoring and rental management system
- Auto-leveling system
- Emergency stop button
- Over tilt protection system
- Emergency descent system
- On-board diagnostic system
- Oscillating axle
- 4.3' LED display
- Load sensing system
- Swing-out engine tray

Accessories & Options

- Platform work lights
- Anti-collision device
- AC power to platform



HIGHLIGHTS

- Better work envelop performance, 10% larger than competitor.
- Zoomlion AWM Remote Monitoring and Rental Management System.
- Industry leading telematic control interface with self-diagnostic monitoring capability.
- Platform dual capacity design, up to 300/454kg.
- Smooth & stable boom extension control as low as 15mm/s.

nash
PLANT GROUP
Sales & Hire
1 3 0 0 6 2 7 4 7 4

ACCESS WITH ZOOMLION GREEN

Hotline: +86 400-800-0157
E-mail: awm@zoomlion.com

Add: ZOOMLION Wangcheng Industrial Park, Tengfei Road 997, Changsha, Hunan, China.
Learn more at <http://en.zoomlion.com/>

MAIN SPECS OF TELESCOPIC BOOM LIFTS

Comply with CE/ANSI/GB Standard

Model	ZT26J	ZT20J
Size		
Work Height	28.20 m	22.75 m
Platform Height	26.20 m	20.75 m
Horizontal Outreach	22.71m	16.80 m
A - Stowed Length	12.5 m	10.36 m
B - Stowed Width	2.49 m	2.49 m
C - Stowed Height	2.80 m	2.78 m
D - Platform Length	2.44 m	2.44 m
E - Platform Width	0.91m	0.91m
F - Wheelbase	3.05 m	2.52 m
Wheelbase	2.05 m	2.13 m
G - Ground Clearance	0.40 m	0.42 m
Performance		
Platform Capacity (Unrestricted/Restricted)	300 kg / 454 kg	300 kg / 454 kg
Drive Speed (Working)	5.5 km/h	6.0 km/h
Gradeability	45% (24°)	45% (24°)
Turning Radius (Inside)	3.66 m	2.4 m
Turning Radius (Outside)	6.86 m	5.4 m
Turntable Swing	360° continuous	360° continuous
Platform Rotation	±90°	±90°
Tail Swing	1.60 m	1.45 m
Jib (Range of Articulation)	130° (-55°~75°)	135°(-60°~75°)
Max. Working Slope	3°	3°
Max. Wind Speed	12.5 m/s	12.5 m/s
Power		
Engine	Deutz TD2.9 L4/ Cummins QSF2.8	Deutz D447 L4/ Perkins 404D-22T
Fuel Tank Capacity	150 L	130 L
Control Voltage	12 V DC	12 V DC
Hydraulic Tank Capacity	150 L	150 L
Drive Mode	4WD	4WD
Steering Mode	Front-wheel	Front-wheel
Tire		
Type	15-625 Foam-filled Tires	355/55D-625 Foam-filled Tires
Weight		
Gross	18900 kg	12200 kg

